




KINGQUAD

4x4 400ASI

KINGQUAD 400ASI SE



The KingQuad 400ASI SE is not eligible for sale in California per California Air Resource Board (CARB) off-highway vehicle regulations.

OVERVIEW

In 1982, Suzuki introduced the world's first 4-wheel ATV. Today, Suzuki ATVs are everywhere. From the most remote areas to the most challenging tasks, you will find the KingQuad powering a rider onward. Across the board, our KingQuad lineup is an exceptional group of ATVs.

Whether you are working hard or getting away from it all, the 2025 Suzuki KingQuad 400ASI SE helps you every step of the way. The fully automatic Quadmatic™ transmission has 2WD and 4WD modes to handle rough trail conditions while completing even the most demanding chores. Along with exceptional engine performance across the powerband, its high-performance iridium spark plug, and Pulsed-secondary AIR-injection (PAIR) system help provide outstanding fuel efficiency and impressive performance.



Armored Blue Gray

2025

KEY FEATURES

- The KingQuad 400ASI's fuel-injected, 376cc, four-stroke, four-valve engine produces efficient power and drivability. Class-leading fuel injection smooths power output and provides excellent cold starting. This system uses 3-D maps for optimum fuel injection and ignition to provide a responsive throttle and emissions compliance.
- The unique Armored Blue Gray bodywork features sharply angled, high-clearance fenders while the full steel cargo racks help tackle any ranch or outdoors task.
- The Quadmatic™ transmission is a fully automatic, CVT (continuously variable transmission) with selectable high/low sub-transmission and reverse for maximum traction and fuel efficiency.
- Select 2WD or 4WD with the flip of a handlebar-mounted lever. The shaft drive system is dependable, durable, and is virtually maintenance-free.
- Independent front A-arm suspension and a dual-shock rear suspension offers smooth performance and remarkable ground clearance with 6.7 inches (170.1 mm) of front and rear wheel travel.
- Dual front hydraulic disc brakes feature calipers with large, 34mm pistons and wide brake-pad surface areas for ample stopping power while providing outstanding durability.
- Large, 4.2-gallon (16.0 L) fuel tank provides outstanding riding range. Suzuki's legendary and plush T-shaped seat is comfortable for short or long rides.
- Large, 25-inch Carlisle® tires with aggressive tread offer consistent traction in wet conditions, yet make for a quiet, smooth ride on hard-packed trails. The tires are mounted to cast aluminum wheels powder-coated with a durable, blacked-out matte finish.
- Each new KingQuad is supplied with a two-year Limited Warranty that is much longer than other ATV warranties. Longer coverage and other benefits are available through Suzuki Extended Protection (SEP).

ENGINE

- The KingQuad 400ASI SE's fuel-injected, 376cc, four-stroke, four-valve engine produces efficient power and drivability.
- Suzuki's class-leading fuel injection smooths power output, especially in the mid-to-high range, and provides excellent cold starting. The system uses 3-D maps for optimum ignition, creating responsive yet environmentally compliant performance.
- Suzuki Advanced Cooling System (SACS) uses an oil cooler and thermostat-controlled cooling fan to shed engine heat during hard work or cargo hauling.
- Push-button electric starting has a start-in-gear function allowing starting without shifting to neutral (as conditions permit).
- The Engine Control Unit (ECU) has slip control logic, which adjusts fuel injector duration and timing to improve drivability and grip in loose/slippery conditions.
- Highly efficient iridium spark plug helps deliver outstanding acceleration, high fuel efficiency and durability.
- Pulsed-secondary AIR-injection (PAIR) system and catalyst-equipped exhaust system help the ATV comply with Environmental Protection Agency (EPA) emission standards while maintaining an elevated level of performance.

TRANSMISSION

- The Quadmatic™ transmission is a fully automatic, CVT (continuously variable transmission) with selectable high/low sub-transmission and reverse for maximum traction and fuel efficiency.
- Automotive gate-type gearshift lever lets you conveniently choose the high or low range, neutral, or reverse.
- Select 2WD and 4WD with the flip of a handlebar-mounted lever. The shaft drive system is dependable and durable and is almost maintenance-free.
- Torque-sensing limited-slip front differential provides maximum traction and light steering when in 4WD mode.
- An advanced engine-braking system minimizes free-wheeling with the throttle off to help control the ATV during steep descents.
- The ECU has a Reverse Mode that monitors vehicle speed so higher engine rpm can be used when getting out of mud or loose soil in reverse mode.

CHASSIS

- Sporty, Armored Blue Gray bodywork features sharply angled, high-clearance fenders.
- Suzuki's plush T-shaped seat delivers rider mobility during sport or difficult terrain riding. Overall length is under 82-inches (208 cm), so the KingQuad fits into a 6.5-foot truck bed for easy transportation.
- Independent front A-arm suspension offers smooth performance and remarkable ground clearance with 6.7 inches (170.1 mm) of wheel travel.
- A swingarm rear suspension with 6.7 inches (170.1 mm) of wheel travel and twin shock absorbers provides agile handling and plush riding.
- Dual front hydraulic disc brakes feature calipers with large, 34mm pistons and wide brake-pad surface area for ample stopping power and outstanding durability. Lightweight and durable plastic skid plates are sturdy to withstand trail pounding, yet slippery to let obstacles slide below.
- The KingQuad 400ASI SE rides on cast aluminum wheels that are powder-coated black.
- Large, 25-inch Carlisle tires with aggressive tread offer consistent traction in wet conditions, yet make for a quiet, smooth ride on hard-packed trails.

UTILITY/CONVENIENCE

- Dual 35-watt headlights (with high- and low-beam settings) are part of the distinctive KingQuad grille appearance. Bright tail light helps make the ATV visible in dark conditions.
- Heavy-duty front and rear cargo racks let you take advantage of the ATV's superb load capabilities. Wrinkle paint finish on the racks and front bumper is durable and scratch resistant.
- LCD instrumentation includes a speedometer, odometer, trip meter, hour meter, clock, fuel gauge, and indicators for reverse, neutral, oil, and FI (fuel injection).
- Automotive-style DC power outlet is included on the front fender.
- Winch-ready mounts and wire conduit make winch installation simple.
- Large, 4.2-gallon (16.0 L) fuel tank provides outstanding riding range.
- Full floorboards with integrated raised footpegs.



ADDITIONAL

- Suzuki's 24-month limited warranty is much longer than other ATV warranties. Longer coverage and other benefits are available through Suzuki Extended Protection (SEP).
- A variety of Genuine Suzuki Accessories are available, including winches, windshield, front and rear bumpers, snowplow, aluminum skid pans, rack extensions, utility box, and more.
- Minimum rider age: 16 years old
- For more details, please visit www.SuzukiCycles.com.

SPECIFICATIONS

ENGINE

Engine:	376cc (22.94 cubic in.), 4-stroke, air-cooled with SCAS, OHC single cylinder
Bore x Stroke:	82.0 mm x 71.2 mm (3.228 in. x 2.803 in.)
Compression Ratio:	9.0:1
Fuel System:	Suzuki electronic fuel injection
Starter:	Electric
Lubrication:	Wet sump

DRIVETRAIN

Clutch:	Dry shoe, automatic, centrifugal type
Transmission:	Automatic variable ratio (V-belt), with high/low range and reverse
Driven Wheels:	2WD and 4WD
Final Drive:	Shaft drive

CHASSIS

Suspension, Front:	Independent, double wishbone, coil spring, oil damped
Suspension, Rear:	Swingarm type, coil spring, oil damped
Brake, Front:	Disc brakes, twin rotors
Brake, Rear:	Single drum brake
Tire, Front:	AT25 x 8-12, tubeless type x 2
Tire, Rear:	AT25 x 10-12, tubeless type x 2
Fuel Tank Capacity:	16.0 L (4.2 US gal.)

ELECTRICAL

Ignition:	Electronic ignition (transistorized)
Headlight:	12V 35/35W (HS1) x 2
Tail Light:	12V 21/5W

DIMENSIONS

Overall Length:	2060 mm (81.1 in.)
Overall Width:	1145 mm (45.1 in.)
Overall Height:	1220 mm (48.0 in.)
Wheelbase:	1270 mm (50.0 in.)
Ground Clearance:	250 mm (9.8 in.)
Seat Height:	840 mm (33.1 in.)
Curb Weight:	265 kg (628 lb.)

WARRANTY

Warranty:	24-month unlimited-mileage limited warranty <i>Longer coverage periods with other benefits are available through Suzuki Extended Protection (SEP).</i>
------------------	---

Suzuki Motor USA, LLC makes every effort to present the most current specifications and product features at the time of publication. Because of our policy of continual improvement, changes may be made in equipment, availability, and specifications without notice or obligation. At Suzuki, we want every ride to be safe and enjoyable. Always wear a helmet, eye protection, and protective clothing. Never ride under the influence of alcohol or other drugs. Study your owner's manual and always inspect your Suzuki before riding. Always supervise young riders. Take a riding skills course. For the nearest ATV skills course, call the SVIA at 1-800-852-5344, and we will even pay for the training. Along with concerned conservationists everywhere, Suzuki urges you to Tread Lightly!® on public and private land. Preserve your future riding opportunities by showing respect for the environment, local laws, and the rights of others when you ride. Limited Warranty: The 2025 KingQuad 400ASI SE limited warranty covers a period of 24 months. See your dealer for details. Ask your participating dealer about Genuine Suzuki Accessories, the Suzuki Retail Finance Plan, and the Suzuki Extended Protection Plan. With the Suzuki Retail Finance Plan, it is easy to afford and equip the machine that is perfect for you. Visit Suzukicycles.com for more information. Suzuki Motor USA, LLC, 3251 East Imperial Highway, P.O. Box 1100, Brea, CA 92822-1100. Suzuki, the "S" logo, and Suzuki model names are Suzuki trademarks or registered trademarks. ©2024 Suzuki Motor USA, LLC